

2023 ITC Women's Team SMYRNA



Oil Pattern Distance **Forward Oil Total Tank Configuration**

42 20.16 mL Multi Tank **Reverse Brush Drop Reverse Oil Total Tank A Conditioner**

37 7.52 mL **Fire** Oil Per Board **Volume Oil Total Tank B Conditioner**

40 ul 27.68 mL Ice

| 1 2L 2R 4 18 3 A 148 0.0 7.6 7.6 5920 2 5L 5R 4 18 3 B 124 7.6 17.8 10.2 4960 3 6L 6R 2 10 3 B 58 17.8 20.6 2.8 2320 4 8L 8R 2 18 3 B 50 20.6 25.7 5.1 2000 5 2L 2R 1 18 3 A 37 25.7 28.2 2.5 1480 6 6L 6R 3 22 3 A 87 28.2 37.5 9.3 3480 | | START | STOP | LOADS | SPEED | BUFFER | TANK | CROSSED | START | END | FEET | T.OIL |
|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---|-------|------|-------|-------|--------|------|---------|-------|------|------|-------|
| 3 6L 6R 2 10 3 B 58 17.8 20.6 2.8 2320 4 8L 8R 2 18 3 B 50 20.6 25.7 5.1 2000 5 2L 2R 1 18 3 A 37 25.7 28.2 2.5 1480 6 6L 6R 3 22 3 A 87 28.2 37.5 9.3 3480 | 1 | 2L | 2R | 4 | 18 | 3 | Α | 148 | 0.0 | 7.6 | 7.6 | 5920 |
| 4 8L 8R 2 18 3 B 50 20.6 25.7 5.1 2000 5 2L 2R 1 18 3 A 37 25.7 28.2 2.5 1480 6 6L 6R 3 22 3 A 87 28.2 37.5 9.3 3480 | 2 | 5L | 5R | 4 | 18 | 3 | В | 124 | 7.6 | 17.8 | 10.2 | 4960 |
| 5 2L 2R 1 18 3 A 37 25.7 28.2 2.5 1480 6 6L 6R 3 22 3 A 87 28.2 37.5 9.3 3480 | 3 | 6L | 6R | 2 | 10 | 3 | В | 58 | 17.8 | 20.6 | 2.8 | 2320 |
| 6 6L 6R 3 22 3 A 87 28.2 37.5 9.3 3480 | 4 | 8L | 8R | 2 | 18 | 3 | В | 50 | 20.6 | 25.7 | 5.1 | 2000 |
| | 5 | 2L | 2R | 1 | 18 | 3 | Α | 37 | 25.7 | 28.2 | 2.5 | 1480 |
| 7 31 30 0 33 3 4 0 375 430 45 0 | 6 | 6L | 6R | 3 | 22 | 3 | Α | 87 | 28.2 | 37.5 | 9.3 | 3480 |
| 7 2L 2R 0 22 3 A 0 37.5 42.0 4.5 0 | 7 | 2L | 2R | 0 | 22 | 3 | Α | 0 | 37.5 | 42.0 | 4.5 | 0 |
| | | | | | | | | | | | | |
| | | | | | | | | | | | | |
| | | | | | | | | | | | | |
| | | | | | | | | | | | | |
| | | | | | | | | | | | | |
| | | | | | | | | | | | | |

| | START | STOP | LOADS | SPEED | BUFFER | TANK | CROSSED | START | END | FEET | T.OIL |
|---|-------|------|-------|-------|--------|------|---------|-------|------|-------|-------|
| 1 | 2L | 2R | 0 | 30 | 3 | В | 0 | 42.0 | 36.0 | -6.0 | 0 |
| 2 | 13L | 13R | 4 | 26 | 3 | В | 60 | 36.0 | 21.3 | -14.7 | 2400 |
| 3 | 7L | 7R | 2 | 26 | 3 | В | 54 | 21.3 | 14.0 | -7.3 | 2160 |
| 4 | 2L | 2R | 2 | 22 | 3 | Α | 74 | 14.0 | 7.8 | -6.2 | 2960 |
| 5 | 2L | 2R | 0 | 10 | 3 | Α | 0 | 7.8 | 0.0 | -7.8 | 0 |
| | | | | | | | | | | | |
| | | | | | | | | | | | |

Cleaner Ratio Main Mix Cleaner Ratio Back End Mix Cleaner Ratio Back End Distance Buffer RPM: 4 = 700 | 3 = 500 | 2 = 200 | 1 = 100

NA NA NA Forward Reverse Combined



| Item | 3L-7L:18L-18R | 8L-12L:18L-18R | 13L-17L:18L-18R | 18L-18R:17R-13R | 18L-18R:12R-8R | 18L-18R:7R-3R |
|------------------|----------------|----------------|-----------------|-----------------|----------------|----------------|
| Description | Outside:Middle | Middle:Middle | Inside:Middle | MIddle: Inside | Middle:Middle | Middle:Outside |
| Track Zone Ratio | 2.03 | 1.2 | 1 | 1 | 1.2 | 2.03 |



