

2 - 2024 ISC Singles (SMYRNA WOMEN)



Oil Pattern Distance **Forward Oil Total Tank Configuration**

13.635 mL **Multi Tank**

37

Reverse Brush Drop Reverse Oil Total Tank A Conditioner

37 12.87 mL **Fire** Oil Per Board **Volume Oil Total Tank B Conditioner**

45 ul 26.505 mL Ice

| 1 2L 2R 2 14 3 A 74 0.0 1.9 1.9 3333 2 5L 5R 2 18 3 A 62 1.9 7.0 5.1 2796 3 7L 7R 2 18 3 B 54 7.0 12.1 5.1 2436 4 8L 8R 2 18 3 B 50 12.1 17.2 5.1 2256 5 10L 10R 3 18 3 B 63 17.2 24.8 7.6 2833 6 2L 2R 0 22 3 B 0 24.8 30.0 5.2 | | START | STOP | LOADS | SPEED | BUFFER | TANK | CROSSED | START | END | FEET | T.OIL |
|--|---|-------|------|-------|-------|--------|------|---------|-------|------|------|-------|
| 3 7L 7R 2 18 3 B 54 7.0 12.1 5.1 2436 4 8L 8R 2 18 3 B 50 12.1 17.2 5.1 2256 5 10L 10R 3 18 3 B 63 17.2 24.8 7.6 2833 | 1 | 2L | 2R | 2 | 14 | 3 | Α | 74 | 0.0 | 1.9 | 1.9 | 3330 |
| 4 8L 8R 2 18 3 B 50 12.1 17.2 5.1 2256 5 10L 10R 3 18 3 B 63 17.2 24.8 7.6 283 | 2 | 5L | 5R | 2 | 18 | 3 | Α | 62 | 1.9 | 7.0 | 5.1 | 2790 |
| 5 10L 10R 3 18 3 B 63 17.2 24.8 7.6 283 | 3 | 7L | 7R | 2 | 18 | 3 | В | 54 | 7.0 | 12.1 | 5.1 | 2430 |
| | 4 | 8L | 8R | 2 | 18 | 3 | В | 50 | 12.1 | 17.2 | 5.1 | 2250 |
| 6 2L 2R 0 22 3 B 0 24.8 30.0 5.2 | 5 | 10L | 10R | 3 | 18 | 3 | В | 63 | 17.2 | 24.8 | 7.6 | 2835 |
| | 6 | 2L | 2R | 0 | 22 | 3 | В | 0 | 24.8 | 30.0 | 5.2 | 0 |
| 7 2L 2R 0 26 3 B 0 30.0 37.0 7.0 | 7 | 2L | 2R | 0 | 26 | 3 | В | 0 | 30.0 | 37.0 | 7.0 | 0 |
| | | | | | | | | | | | | |
| | | | | | | | | | | | | |
| | | | | | | | | | | | | |
| | | | | | | | | | | | | |
| | | | | | | | | | | | | |
| | | | | | | | | | | | | |

| | START | STOP | LOADS | SPEED | BUFFER | TANK | CROSSED | START | END | FEET | T.OIL |
|---|-------|------|-------|-------|--------|------|---------|-------|------|------|-------|
| 1 | 2L | 2R | 0 | 30 | 3 | В | 0 | 37.0 | 30.0 | -7.0 | 0 |
| 2 | 9L | 9R | 2 | 18 | 3 | В | 46 | 30.0 | 24.9 | -5.1 | 2070 |
| 3 | 8L | 8R | 2 | 18 | 3 | В | 50 | 24.9 | 19.8 | -5.1 | 2250 |
| 4 | 7L | 7R | 2 | 14 | 3 | В | 54 | 19.8 | 15.9 | -3.9 | 2430 |
| 5 | 5L | 5R | 2 | 14 | 3 | Α | 62 | 15.9 | 12.0 | -3.9 | 2790 |
| 6 | 2L | 2R | 2 | 14 | 3 | Α | 74 | 12.0 | 8.1 | -3.9 | 3330 |
| 7 | 2L | 2R | 0 | 14 | 3 | Α | 0 | 8.1 | 0.0 | -8.1 | 0 |
| l | | | | | | | | | | | |
| 1 | | | | | | | | | | | |

Cleaner Ratio Main Mix Cleaner Ratio Back End Mix Cleaner Ratio Back End Distance Buffer RPM: 4 = 700 | 3 = 500 | 2 = 200 | 1 = 100

NA NA NA Forward Reverse Combined



| Item | 3L-7L:18L-18R | 8L-12L:18L-18R | 13L-17L:18L-18R | 18L-18R:17R-13R | 18L-18R:12R-8R | 18L-18R:7R-3R |
|------------------|----------------|----------------|-----------------|-----------------|----------------|----------------|
| Description | Outside:Middle | Middle:Middle | Inside:Middle | MIddle: Inside | Middle:Middle | Middle:Outside |
| Track Zone Ratio | 2,92 | 1.08 | 1 | 1 | 1.08 | 2.92 |



